

**AMENDMENTS TO THE CLAIMS**

**IN THE CLAIMS:**

This Listing of Claims will replace all prior versions, and listings, of claims in the subject Patent Application:

**Listing of Claims:**

1. (Currently amended) Computer-readable media tangibly embodying a key-caching program executable on a computer and operating on a packet received from an external source, the computer including a system memory and a cache, the system memory and the cache including entries for source addresses and corresponding keys, the packet including a header that is not encrypted and a body that is encrypted, the key-caching program comprising code for:

establishing acknowledgment-responsive wireless communication with the external source;

extracting from the header a source address;

determining whether the source address is included in an entry in the cache;

when the source address is included in an entry of the cache, authorizing an acknowledgment signal for the external source, extracting from the entry of the cache a key corresponding to the source address, and using the key to decrypt the body of the packet;

when the source address is not included in an entry of the cache,  
determining whether the source address is included in an entry of the system  
memory; and

when the source address is not included in an entry of the cache and the  
source address is included in an entry of the system memory, extracting from the  
entry of the system memory a key corresponding to the source address, and storing  
the source address and the key as a new entry in the cache to prepare the cache for  
decrypting a packet subsequently re-sent by the external source.

2. (Original) Computer-readable media as claimed in claim 1, wherein the key-  
caching program further comprises code to effect:

when the source address is not included in an entry of the cache, dropping  
the packet .

3. (Currently amended) Computer-readable media as claimed in claim 1,  
wherein the key-caching program further comprises code to effect:

when the source address is not included in an entry of the cache,  
authorizing an acknowledgment signal for anticipatory transmission to the external  
source of the packet prior to retrieval of the key corresponding to the source  
address; and

when the source address is not included in an entry of the cache and the source address is included in an entry of the system memory, using the key to decrypt the body of the packet prior to arrival of a subsequent packet from the external source.

4. (Original) Computer-readable media as claimed in claim 1, wherein the cache includes fast memory.

5. (Original) Computer-readable media as claimed in claim 2, wherein the cache includes fast memory.

6. (Original) Computer-readable media as claimed in claim 3, wherein the cache includes fast memory.

7. (Currently amended) A key-caching system for operation on a packet received from an external source, the packet comprising a header that is not encrypted and a body that is encrypted, the key-caching system comprising:

a system memory,

a networking unit, the networking unit including a cache, the system memory and the cache including entries for source addresses and corresponding keys,

a processor, the system memory including a key-caching program that is executable on the processor, and

a controller, the controller effecting communication and data transfer between the system memory, the networking unit and the processor, wherein the key-caching program comprising code to effect:

establishing acknowledgment-responsive wireless communication with the external source;

extracting from the header a source address;

determining whether the source address is included in an entry in the cache;

when the source address is included in an entry of the cache, authorizing an acknowledgment signal for the external source, extracting from the entry of the cache a key corresponding to the source address, and using the key to decrypt the body of the packet;

when the source address is not included in an entry of the cache, determining whether the source address is included in an entry of the system memory; and

when the source address is not included in an entry of the cache and the source address is included in an entry of the system memory, extracting from the entry of the system memory a key corresponding to the source address, and storing the source address and the key as a new entry in the cache to prepare the cache for decrypting a packet subsequently re-sent by the external source.

8. (Original) A key-caching system as claimed in claim 7, wherein the key-caching program further comprises code to effect:

when the source address is not included in an entry of the cache, dropping the packet.

9. (Currently amended) A key-caching system as claimed in claim 7, wherein the key-caching program further comprises code to effect:

when the source address is not included in an entry of the cache, authorizing an acknowledgment signal for anticipatory transmission to the external source of the packet prior to retrieval of the key corresponding to the source address; and

when the source address is not included in an entry of the cache and the source address is included in an entry of the system memory, using the key to decrypt the body of the packet prior to arrival of a subsequent packet from the external source.

10. (Original) A key-caching system as claimed in claim 7, wherein the cache includes fast memory.

11. (Original) A key-caching system as claimed in claim 8, wherein the cache includes fast memory.

12. (Original) A key-caching system as claimed in claim 9, wherein the cache includes fast memory.

13. (Currently amended) A method of key caching with a system memory and a cache, the system memory and the cache including entries for source addresses and corresponding keys, the method comprising:

establishing acknowledgment-responsive wireless communication with an external source;

receiving a packet from ~~an~~ the external source, the packet including a header that is not encrypted and a body that is encrypted;

extracting from the header a source address;

determining whether the source address is included in an entry in the cache, authorizing an acknowledgment signal for the external source, extracting from the entry of the cache a key corresponding to the source address, and using the key to decrypt the body of the packet;

when the source address is not included in an entry of the cache, determining whether the source address is included in an entry of the system memory; and

when the source address is not included in an entry of the cache and the source address is included in an entry of the system memory, extracting from the entry of the system memory a key corresponding to the source address, and storing the source address and the key as a new entry in the cache to prepare the cache for decrypting a packet subsequently re-sent by the external source.

14. (Original)        A method of key caching as claimed in claim 13, further comprising:

when the source address is not included in an entry of the cache, dropping the packet.

15. (Currently amended)    A method of key caching as claimed in claim 13, further comprising:

when the source address is not included in an entry of the cache, authorizing an acknowledgment signal for anticipatory transmission to the external source of the packet prior to retrieval of the key corresponding to the source address; and

when the source address is not included in an entry of the cache and the source address is included in an entry of the system memory, using the key to decrypt the body of the packet prior to arrival of a subsequent packet from the external source.

16. (Original) A method of key caching as claimed in claim 13, wherein the cache includes fast memory.

17. (Original) A method of key caching as claimed in claim 14, wherein the cache includes fast memory.

18. (Original) A method of key caching as claimed in claim 15, wherein the cache includes fast memory.